

MANUFACTURE OF PRESSURE RESISTANT SYNTHETIC RESIN PIPE

Publication number: JP4208439

Publication date: 1992-07-30

Inventor: NAGAYOSHI AKIO; NAGAYOSHI SEIJI

Applicant: YUUSHII SANGIYOU KK

Classification:

- international: **B29C53/58; B29C63/22; B29C70/06; B29D23/18; B32B1/08; B32B7/02; F16L9/12; B29K105/08; B29C53/00; B29C63/00; B29C70/06; B29D23/18; B32B1/00; B32B7/02; F16L9/00; (IPC1-7): B29C53/58; B29C63/22; B29C67/14; B29K105/08; B29L23/22; B32B1/08; B32B7/02; F16L9/12**

- european:


Application number: JP19900339440 19901130

Priority number(s): JP19900339440 19901130

[Report a data error here](#)

Abstract of JP4208439

PURPOSE:To manufacture the pressure resistant synthetic resin pipe having good appearance, a high accuracy and excellent pressure resistance by a method wherein a reinforcing material is fed in a spiral form into a spiral groove between the spiral projections of the preformed synthetic resin pipe rotating about its axis, while a thin strip-like steel plate having a predetermined width is being formed into the reinforcing material having a suitable cross sectional configuration by a shaping instrument. **CONSTITUTION:**Both sides of the lower peripheral part of a synthetic resin pipe 1 provided with a hollow spiral projection 2 around the outer peripheral surface of a cylindrical pipe wall 1a integrally therewith are receivably held by rotary feeding rolls 4 and a reinforcing material 5 bent into a U-shaped cross-sectional configuration is continuously fed for engagement with a spiral groove 3 between the spiral projections 2 of the synthetic resin pipe 1 adapted to move forward while rotating on the rolls 4. Upon feeding the reinforcing material 5 into the spiral groove 3 of the synthetic resin pipe 1, through almost one complete revolution of the pipe, the reinforcing material 5 is gradually inserted into the spiral groove 3 by a shaping roller 8, while being moved in a standing position with both its side faces 5b urged against both side wall surfaces of the spiral groove 3 and entirely held against the facing sides of the spiral groove 3. This reinforcing material 5 is enclosed with a synthetic resin strip-like



material 9 composed of the same material as
the synthetic resin pipe 1 to form a resin layer
11.

Data supplied from the **esp@cenet** database - Worldwide